Industrial Pressure Transmitter

Model: PT124B-216 (LED display)

ZHYQ

Description


Adopting global advanced electron ceramic technology, PT124B-216 (LED display) with low range has the character of overload resistance, high impact resistance, excellent linearity, lasting high stability, wide temperature range, corrosion proof, etc. This series can be applied in Defense industry, scientific research, Space industry, Petroleum, Chemical industry, Electric power, Ocean and other fields.



Application

- Defense industry, Scientific research, Space industry
- Petroleum, Chemical industry
- Electric power ,Ocean and other fields
 Feature
- Pressure Range:0....10mbar to 0....10bar
- Measuring element: no medium liquid
- Ceramics technology,
- High accuracy, stable capability, little temp-draft
- overload resistance ,high impact resistance, excellent linearity
- Lasting high stability
- Wide temperature range, corrosion proof

Dimension





Specification

Range:	01bar to 010bar
Accuracy:	0.5%FS
Nonlinearity:	0.2%FS
Reliability:	0.05%FS
Output:	4-20mA (2 Wire)
Input voltage:	24(12~36)VDC (Amplify signal)
Operat Temperature:	-40~80° ℃
Compensated temperature:	0~70 ℃
Overload pressure:	150%FS
Medium material:	stainless steel
Electric connector:	Hirschman (Big DIN)
Process connector:	G1/4, G1/2, 1/2NPT, 1/4NPT, M12*1.5 (Customer design)

Wiring code

Electric connector	2 wire(4-20mA)			3 wire (0-10V, 0-5V, 0.5-4.5V)		
Hirschman	Pin	Function	Color	Pin	Function	Color
$ \begin{array}{c} 3 \\ $	1	E+/S+	Red	1	E+	Red
	2	E-/S-	Black	2	S+	Blue
	3			3	E-/S-	Black

Ordering Guide

Model	Range(bar)	Output	Screw	Electric	Other requirement			
			Thread	connection				
PT124B-216								
Example: PT124B-216-50Bar-4/20mA-G1/2-Hirschmann								

Shanghai Zhaohui Pressure Apparatus Co., Ltd

5-6F No.8 Building No.115 ,Lane 1276 Nanle Road Songjiang District Shanghai 201600 China Tel:+86-21-51691919 67755189 Fax:+86-21-67755185 E-mail: info@zhyqsensor.com www.zhyqsensor.com



ZHYQ Sensor & Control

Page 2 of 2