

# JB-750 yellow 750 V , connection cable für warning indication, flexible, colour coded, meter marking



## Technical data

- Special-PVC connection cable for warning indication adapted to DIN VDE 0285-525-2-11 / DIN EN 50525-2-11
- **Temperature range**  
flexing -15°C to +80°C  
fixed installation -40°C to +80°C
- **Nominal voltage**  $U_0/U$  450/750 V
- **Test voltage** 4000 V
- **Breakdown voltage** min. 8000 V
- **Insulation resistance**  
min. 20 MΩm x km
- **Minimum bending radius**  
flexing 7,5x cable Ø  
fixed installation 4x cable Ø
- **Radiation resistance**  
up to  $80 \times 10^6$  cJ/kg (up to 80 Mrad)

## Cable structure

- Bare copper-conductor, to DIN VDE 0295 cl.5, fine-wire, BS 6360 cl.5, IEC 60228 cl.5
- Core insulation of special PVC compound type T12 to DIN VDE 0207-363-3 / DIN EN 50363-3
- Core identification to DIN VDE 0293
- GN-YE conductor
- Cores stranded in layers with optimal lay-length
- Outer sheath of special PVC compound type TM2 to DIN VDE 0207-363-4-1 / DIN EN 50363-4-1
- Sheath colour yellow (RAL 1016)
- with meter marking

## Properties

- Extensively oil resistant, oil-/chemical resistance see table Technical Informations
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

## Tests

- PVC self-extinguishing and flame retardant acc. to DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)

## Note

- G = with green-yellow conductor
- AWG sizes are approximate equivalent values. The actual cross-section is in mm<sup>2</sup>.

## Application

These cables are used for flexible use for medium mechanical stresses with free movement without tensile stress or forced movements in dry, moist and wet rooms but not suitable for open air, as connection cable with yellow outer sheath as a special warning indication. Recommendation in accordance to EN 60204 part 1 and DIN VDE 0113 part 1.

CE= The product is conformed with the EC Low-Voltage Directive 2006/95/EC.

Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
10334	3 G 1,5	7,8	43,0	100,0	16
10335	4 G 1,5	8,5	58,0	121,0	16
10336	5 G 1,5	9,6	72,0	148,0	16

Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
10337	3 G 2,5	9,3	72,0	154,0	14
10338	4 G 2,5	10,2	96,0	208,0	14
10339	5 G 2,5	11,4	120,0	229,0	14

Dimensions and specifications may be changed without prior notice. (RA01)



Suitable accessories can be found in Chapter X.

- Cable Gland - HELUTOP® HT-PA
- Cable Gland - HELUTOP® HT-MS