

JZ-500 HMH flexible control cable, halogen-free, extremely fire resistant, oil resistant¹⁾, meter marking



Technical data

- Halogen-free flexible control cable adapted to
DIN VDE 0285-525-2-51 /
DIN EN 50525-2-51 and
DIN VDE 0285-525-3-11 /
DIN EN 50525-3-11
- **Temperature range**
flexing -15°C to +70°C
fixed installation -40°C to +70°C
- **Nominal voltage** U_0/U 300/500 V
- **Test voltage** 2000 V
- **Minimum bending radius**
flexing 12,5x cable Ø
fixed installation 4x cable Ø
- **Radiation resistance**
up to 100x10⁶ cJ/kg (up to 100 Mrad)

Cable structure

- Bare copper-conductor, to
DIN VDE 0295 cl.5, fine-wire,
BS 6360 cl.5, IEC 60228 cl.5
- Core insulation of halogen-free polymer compound type T16 to
DIN VDE 0207-363-7 / DIN EN 50363-7
- Core identification to DIN VDE 0293
black cores with continuous white numbering
- GN-YE conductor, 3 cores and above in the outer layer
- Cores stranded in layers with optimal lay-length
- Outer sheath of halogen-free polymer compound type TM7 to
DIN VDE 0207-363-8 / DIN EN 50363-8
- Outer Sheath colour grey (RAL 7001)
- with meter marking
- **LS0H**= Low Smoke Zero Halogen

Properties

- ¹⁾ For the critical applications we advise for consultation
 - The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers
- ### Tests
- Flame test acc. to
DIN VDE 0482-332-3, BS 4066 part 3,
DIN EN 60332-3, IEC 60332-3 (previously
DIN VDE 0472 part 804 test method C)
 - self-extinguishing and flame retardant
acc. to DIN VDE 0482-332-1-2,
DIN EN 60332-1-2, IEC 60332-1 (equivalent
DIN VDE 0472 part 804 test method B)
 - Corrosiveness of combustion gases
acc. to DIN VDE 0482 part 267,
DIN EN 50267-2-2, IEC 60754-2
(equivalent DIN VDE 0472 part 813)
 - Halogen-free acc. to DIN VDE 0482
part 267, DIN EN 50267-2-1, IEC 60754-1
(equivalent DIN VDE 0472 part 815)
 - Smoke density acc. to DIN VDE 0482
part 1034-1+2, DIN EN 61034-1+2,
IEC 61034-1+2, BS 7622 part 1+2
(previously DIN VDE 0472 part 816)

Note

- G = with green-yellow conductor
x = without green-yellow conductor (OZ)
- AWG sizes are approximate equivalent values. The actual cross-section is in mm².
- Please note the cleanroom qualification when ordering.
- screened analogue type:
JZ-500 HMH-C, confer page 96

Application

Used as measuring, monitoring and control cables in tool machinery, conveyor belts, production lines, in plant, in air-conditioning, in foundries and steel mills. For fixed installation or flexible application, casual, not constantly recurring free movement without forced motion and without tensile stress, for medium mechanical stress. The cable is suitable for use in dry, damp and wet locations and on plaster.

CE= The product is conformed with the EC Low-Voltage Directive 2006/95/EC.

Part no.	No. cores x cross-sec. mm ²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
11201	2 x 0,5	4,8	9,6	43,0	20
11202	3 G 0,5	5,1	14,4	50,0	20
11332	3 x 0,5	5,1	14,4	50,0	20
11203	4 G 0,5	5,6	19,0	60,0	20
11333	4 x 0,5	5,5	19,0	60,0	20
11204	5 G 0,5	6,2	24,0	71,0	20
11334	5 x 0,5	6,2	24,0	71,0	20
11205	7 G 0,5	6,7	33,6	84,0	20
11206	8 G 0,5	7,4	38,0	101,0	20
11207	10 G 0,5	8,3	48,0	121,0	20
11208	12 G 0,5	8,7	58,0	142,0	20
11209	16 G 0,5	10,0	76,0	183,0	20

Part no.	No. cores x cross-sec. mm ²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
11210	18 G 0,5	10,7	86,0	204,0	20
11211	20 G 0,5	11,3	96,0	227,0	20
11212	25 G 0,5	12,6	120,0	283,0	20
11213	30 G 0,5	13,5	144,0	324,0	20
11214	34 G 0,5	14,3	163,0	367,0	20
11215	37 G 0,5	14,5	178,0	381,0	20
11216	41 G 0,5	15,8	197,0	417,0	20
11217	42 G 0,5	15,8	202,0	454,0	20
11218	50 G 0,5	17,5	240,0	519,0	20
11219	61 G 0,5	18,5	293,0	635,0	20
11220	65 G 0,5	19,4	312,0	694,0	20

Continuation ▶

JZ-500 HMH flexible control cable, halogen-free, extremely fire resistant, oil resistant¹⁾, meter marking



A

Part no.	No. cores x cross-sec. mm ²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
11221	2 x 0,75	5,3	14,4	47,0	19
11222	3 G 0,75	5,6	21,6	56,0	19
11223	3 x 0,75	5,6	21,6	56,0	19
11223	4 G 0,75	6,3	29,0	69,0	19
11224	4 x 0,75	6,3	29,0	69,0	19
11224	5 G 0,75	6,9	36,0	83,0	19
11224	5 G 0,75	6,9	36,0	83,0	19
11225	7 G 0,75	7,5	50,0	114,0	19
11225	7 G 0,75	7,5	50,0	114,0	19
11226	8 G 0,75	8,3	58,0	136,0	19
11226	8 G 0,75	8,3	58,0	136,0	19
11227	10 G 0,75	9,2	72,0	172,0	19
11227	10 G 0,75	9,2	72,0	172,0	19
11228	12 G 0,75	9,8	86,0	183,0	19
11228	12 G 0,75	9,8	86,0	183,0	19
11229	16 G 0,75	11,4	115,0	241,0	19
11229	16 G 0,75	11,4	115,0	241,0	19
11230	18 G 0,75	12,2	130,0	266,0	19
11230	18 G 0,75	12,2	130,0	266,0	19
11231	20 G 0,75	12,7	144,0	291,0	19
11231	20 G 0,75	12,7	144,0	291,0	19
11232	25 G 0,75	14,3	180,0	374,0	19
11232	25 G 0,75	14,3	180,0	374,0	19
11233	30 G 0,75	15,3	216,0	450,0	19
11233	30 G 0,75	15,3	216,0	450,0	19
11234	34 G 0,75	16,5	245,0	517,0	19
11234	34 G 0,75	16,5	245,0	517,0	19
11235	37 G 0,75	16,7	260,0	541,0	19
11235	37 G 0,75	16,7	260,0	541,0	19
11236	41 G 0,75	18,1	296,0	611,0	19
11236	41 G 0,75	18,1	296,0	611,0	19
11237	42 G 0,75	18,1	302,0	621,0	19
11237	42 G 0,75	18,1	302,0	621,0	19
11238	50 G 0,75	19,8	360,0	742,0	19
11238	50 G 0,75	19,8	360,0	742,0	19
11239	61 G 0,75	21,2	439,0	853,0	19
11239	61 G 0,75	21,2	439,0	853,0	19
11240	65 G 0,75	21,8	468,0	909,0	19
11240	65 G 0,75	21,8	468,0	909,0	19
11241	2 x 1	5,6	19,2	63,0	18
11241	2 x 1	5,6	19,2	63,0	18
11242	3 G 1	5,9	29,0	74,0	18
11242	3 G 1	5,9	29,0	74,0	18
11243	3 x 1	5,9	29,0	74,0	18
11243	4 G 1	6,6	38,4	90,0	18
11243	4 G 1	6,6	38,4	90,0	18
11244	4 x 1	6,6	38,4	90,0	18
11244	5 G 1	7,3	48,0	109,0	18
11244	5 G 1	7,3	48,0	109,0	18
11245	7 G 1	8,1	67,0	151,0	18
11245	7 G 1	8,1	67,0	151,0	18
11246	8 G 1	8,8	77,0	184,0	18
11246	8 G 1	8,8	77,0	184,0	18
11247	10 G 1	9,8	96,0	224,0	18
11247	10 G 1	9,8	96,0	224,0	18
11248	12 G 1	10,4	115,0	243,0	18
11248	12 G 1	10,4	115,0	243,0	18
11249	16 G 1	12,3	154,0	314,0	18
11249	16 G 1	12,3	154,0	314,0	18
11250	18 G 1	12,9	173,0	361,0	18
11250	18 G 1	12,9	173,0	361,0	18
11251	20 G 1	13,8	192,0	387,0	18
11251	20 G 1	13,8	192,0	387,0	18
11252	25 G 1	15,4	240,0	496,0	18
11252	25 G 1	15,4	240,0	496,0	18
11253	34 G 1	17,7	326,0	670,0	18
11253	34 G 1	17,7	326,0	670,0	18
11254	37 G 1	17,9	355,0	713,0	18
11254	37 G 1	17,9	355,0	713,0	18
11255	41 G 1	19,5	394,0	784,0	18
11255	41 G 1	19,5	394,0	784,0	18
11256	42 G 1	19,5	403,0	824,0	18
11256	42 G 1	19,5	403,0	824,0	18
11257	50 G 1	21,3	480,0	952,0	18
11257	50 G 1	21,3	480,0	952,0	18
11258	61 G 1	22,5	586,0	1140,0	18
11258	61 G 1	22,5	586,0	1140,0	18
11259	65 G 1	23,6	628,0	1201,0	18
11259	65 G 1	23,6	628,0	1201,0	18
11260	2 x 1,5	6,4	29,0	70,0	16
11260	2 x 1,5	6,4	29,0	70,0	16
11261	3 G 1,5	6,8	43,0	94,0	16
11261	3 G 1,5	6,8	43,0	94,0	16
11262	3 x 1,5	6,8	43,0	94,0	16
11262	4 G 1,5	7,4	58,0	112,0	16
11262	4 G 1,5	7,4	58,0	112,0	16
11263	5 G 1,5	8,3	72,0	141,0	16
11263	5 G 1,5	8,3	72,0	141,0	16
11264	7 G 1,5	9,2	101,0	191,0	16
11264	7 G 1,5	9,2	101,0	191,0	16
11265	8 G 1,5	10,0	115,0	224,0	16
11265	8 G 1,5	10,0	115,0	224,0	16
11266	10 G 1,5	10,9	144,0	282,0	16
11266	10 G 1,5	10,9	144,0	282,0	16
11267	12 G 1,5	11,8	173,0	311,0	16
11267	12 G 1,5	11,8	173,0	311,0	16
11268	16 G 1,5	13,9	230,0	392,0	16
11268	16 G 1,5	13,9	230,0	392,0	16
11269	18 G 1,5	14,6	259,0	450,0	16
11269	18 G 1,5	14,6	259,0	450,0	16
11270	20 G 1,5	15,6	288,0	497,0	16
11270	20 G 1,5	15,6	288,0	497,0	16
11271	25 G 1,5	17,4	360,0	630,0	16
11271	25 G 1,5	17,4	360,0	630,0	16
11272	34 G 1,5	20,2	490,0	842,0	16
11272	34 G 1,5	20,2	490,0	842,0	16
11273	37 G 1,5	20,2	533,0	897,0	16
11273	37 G 1,5	20,2	533,0	897,0	16
11274	50 G 1,5	24,2	720,0	1277,0	16
11274	50 G 1,5	24,2	720,0	1277,0	16
11275	61 G 1,5	25,8	878,0	1460,0	16
11275	61 G 1,5	25,8	878,0	1460,0	16
11276	65 G 1,5	26,8	936,0	1612,0	16
11276	65 G 1,5	26,8	936,0	1612,0	16

Part no.	No. cores x cross-sec. mm ²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
11277	2 x 2,5	7,8	48,0	118,0	14
11277	2 x 2,5	7,8	48,0	118,0	14
11278	3 G 2,5	8,3	72,0	151,0	14
11278	3 G 2,5	8,3	72,0	151,0	14
11279	4 G 2,5	9,2	96,0	181,0	14
11279	4 G 2,5	9,2	96,0	181,0	14
11280	5 G 2,5	10,1	120,0	224,0	14
11280	5 G 2,5	10,1	120,0	224,0	14
11281	7 G 2,5	11,2	168,0	316,0	14
11281	7 G 2,5	11,2	168,0	316,0	14
11282	8 G 2,5	12,3	192,0	370,0	14
11282	8 G 2,5	12,3	192,0	370,0	14
11283	10 G 2,5	14,0	240,0	451,0	14
11283	10 G 2,5	14,0	240,0	451,0	14
11284	12 G 2,5	14,8	288,0	499,0	14
11284	12 G 2,5	14,8	288,0	499,0	14
11285	16 G 2,5	17,1	384,0	720,0	14
11285	16 G 2,5	17,1	384,0	720,0	14
11286	18 G 2,5	18,2	432,0	769,0	14
11286	18 G 2,5	18,2	432,0	769,0	14
11287	20 G 2,5	19,2	480,0	911,0	14
11287	20 G 2,5	19,2	480,0	911,0	14
11288	25 G 2,5	21,6	600,0	1047,0	14
11288	25 G 2,5	21,6	600,0	1047,0	14
11289	30 G 2,5	23,0	720,0	1280,0	14
11289	30 G 2,5	23,0	720,0	1280,0	14
11290	2 x 4	9,3	77,0	199,0	12
11290	2 x 4	9,3	77,0	199,0	12
11291	3 G 4	9,8	115,0	247,0	12
11291	3 G 4	9,8	115,0	247,0	12
11292	4 G 4	10,9	154,0	299,0	12
11292	4 G 4	10,9	154,0	299,0	12
11293	5 G 4	12,1	192,0	369,0	12
11293	5 G 4	12,1	192,0	369,0	12
11294	7 G 4	13,2	269,0	463,0	12
11294	7 G 4	13,2	269,0	463,0	12
11295	8 G 4	14,7	307,0	601,0	12
11295	8 G 4	14,7	307,0	601,0	12
11296	10 G 4	17,5	384,0	698,0	12
11296	10 G 4	17,5	384,0	698,0	12
11297	12 G 4	17,7	461,0	790,0	12
11297	12 G 4	17,7	461,0	790,0	12
11298	16 G 4	20,3	614,0	1130,0	12
11298	16 G 4	20,3	614,0	1130,0	12
11299	18 G 4	21,6	691,0	1280,0	12
11299	18 G 4	21,6	691,0	1280,0	12
11300	2 x 6	11,0	115,0	266,0	10
11300	2 x 6	11,0	115,0	266,0	10
11301	3 G 6	11,9	173,0	360,0	10
11301	3 G 6	11,9	173,0	360,0	10
11302	4 G 6	13,0	230,0	429,0	10
11302	4 G 6	13,0	230,0	429,0	10
11303	5 G 6	14,5	288,0	529,0	10
11303	5 G 6	14,5	288,0	529,0	10
11304	7 G 6	16,2	403,0	631,0	10
11304	7 G 6	16,2	403,0	631,0	10
11305	2 x 10	13,8	192,0	440,0	8
11305	2 x 10	13,8	192,0	440,0	8
11306	3 G 10	14,9	288,0	550,0	8
11306	3 G 10	14,9	288,0	550,0	8
11307	4 G 10	16,5	384,0	708,0	8
11307	4 G 10	16,5	384,0	708,0	8
11308	5 G 10	18,3	480,0	862,0	8
11308	5 G 10	18,3	480,0	862,0	8
11309	7 G 10	20,2	672,0	1124,0	8
11309	7 G 10	20,2	672,0	1124,0	8
11310	2 x 16	16,8	307,0	642,0	6
11310	2 x 16	16,8	307,0	642,0	6
11311	3 G 16	18,3	461,0	830,0	6
11311	3 G 16	18,3	461,0	830,0	6
11312	4 G 16	20,1	614,0	1060,0	6
11312	4 G 16	20,1	614,0	1060,0	6
11313	5 G 16	22,6	768,0	1270,0	6
11313	5 G 16	22,6	768,0	1270,0	6
11314	7 G 16	24,8	1075,0	1794,0	6
11314	7 G 16	24,8	1075,0	1794,0	6
11315	3 G 25	22,3	720,0	1190,0	4
11315	3 G 25	22,3	720,0	1190,0	4
11316	4 G 25	25,0	960,0	1594,0	4
11316	4 G 25	25,0	960,0	1594,0	4
11317	5 G 25	27,7	1200,0	2014,0	4