

MDR-60W单组输出导轨电源

MDR-60W Single output DIN rail power supply

概述 Summary

- > 单组输出: 功率60W
Single output: power 60W
- > 输入电压: 85 ~ 264VAC 120 ~ 370VDC
Input voltage: 85 ~ 264VAC 120 ~ 370VDC



常见规格 General Specification

40 × 90 × 100mm

性能 Specification	型号 Model	MDR-60-5	MDR-60-12	MDR-60-24	MDR-60-48
直流输出电压、电流 DC output voltage, current		5V 0 ~ 10A	12V 0 ~ 5A	24V 0 ~ 2.5A	48V 0 ~ 1.25A
纹波及噪音 Wave and noise		80mVp-p	120mVp-p	150mVp-p	200mVp-p
进线稳定度 Inlet wire stability		± 1%	± 1%	± 1%	± 1%
负载稳定度 Load stability		± 1.5%	± 1%	± 1%	± 1%
效率 Efficiency		76%	80%	81%	84%
直流电压可调范围 Adjustable range for DC voltage		± 2%	± 1%	± 1%	± 1%
输入电压范围 Input voltage range	85 ~ 264VAC 120 ~ 370VDC 47 ~ 63Hz				
冲击电流 Impact current	冷启动电流 Cold start current 30A/115VAC 60A/230VAC				
过载保护 Overload protection	105% ~ 150%切断输出, 自动恢复 105% ~ 150% cut off the output, automatic recovery				
过电压保护 Over voltage protection	120% ~ 140%关闭输出, 电源重启后可恢复输出 120% ~ 140% shut down O/P voltage, re-power on to recover				
启动、上升、保持时间 Setup, rise, hold up time	500ms, 30ms/230VAC 满负载 at full load 500ms, 30ms/115VAC 满负载 at full load				
耐压性 Withstand voltage	输入输出间: 1.5kV 输入与外壳间: 1.5kV 输出与外壳间: 0.5kV 一分钟 I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute				
隔离电阻 Isolation resistance	输入输出间 输入与外壳间 输出与外壳间: 500VDC/100MΩ I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ				
工作温度 Working temperature	-10°C ~ +50°C				
尺寸 Dimension	40 × 90 × 100mm				
重量 Weight	0.33kg				
包装 Packing	45.5 × 32.5 × 23CM/60PCS/20kg				

外形尺寸 Overall dimension(mm)

