

## Proop 7 Control

7 inch Professional Operator Panel

7" high resolution TFT LCD display  
 Internal digital input / output features  
 Ethernet, RS-232 and RS-485 communication  
 Optional WiFi and 2nd Ethernet input  
 Process monitoring / control  
 Remote monitoring / control

Share :



Features	Descriptions
<b>Graphics / Visual Features</b>	
Display Type	7 inc TFT
Display colors	260K color
Resolution	800x480
Storage / Operating Temperature	-20 °C with +60 °C / 0 °C with +50 °C
Physical Features	90 % max. (None condensing)
Dimensions	206 mm x 152 mm 50 mm
Panel section	190 x136 mm
Weight	Approximately 700g
<b>Technical Specifications</b>	
Digital Inputs	4
Digital Outputs	4
Analogue Inputs	None
Analogue Outputs	None
Serial Communication-2	RS-485 (Terminal) Maks. Hız : 57600
Serial Communication-3	RS-232 (Terminal) Maks. Hız : 230400
Serial Communication-4	RS-232 (DB-9 socket)
MCU	ARM Cortex-A Series
Flash Memory	8GB eMMC

<b>RAM</b>	512 MB DDR3 SDRAM
<b>Buzzer</b>	Build in >=85 dB
<b>USB Device</b>	1 x USB 2.0
<b>USB Host</b>	1 x USB 2.0
<b>Optional Communication</b>	Wi-Fi (IEEE 80211 b/g/n), Ethernet (10/100 mbps full Duplex)
<b>Communication Protocols</b>	Modbus-RTU, Modbus-ASCII, Modbus TCP/IP, Modbus-ASCII (Slave), Modbus-RTU (Slave), Modbus TCP/IP (Slave), ISOTCP (S7-300 , S7-400, S7-1200, S7-1500), BACNET MS/TP, BACNET IP
<b>Approvals</b>	CE , EAC