



赛普 CEE/IEC 国际标准 自动卷心器

CEE/IEC INTERNATIONAL STANDARD MOBILE POWER SOCKET BOX

符合欧洲/国际标准 EN/IEC 60309-2
Conform to European / international standards EN/IEC 60309-2



产品特点 Feature

独创高耐磨性多重密封技术, 永不漏气
独创多组合、多重导电连接机构, 确保电源稳定输送
独创线管收缩力可调整结构
独家配置耐寒、耐磨、耐油、高性能专用线缆
产品采用高分子材料制造、全封闭式结构, 全新时代设计
自动排管, 避免线管互相缠绕
不锈钢排线出口, 减少线管摩擦
钢质主轴不易断裂, 经久耐用
双侧钢珠轴承更加润滑, 延长产品使用寿命
使用钢质棘爪座, 不易变形, 不易错位
可180度挪动, 方便使用
配置移动式安装结构, 拆装移动方便
使用汽保专用自锁快速接头, 耐高压
工作压力: 1~16KGF/cm², 工作温度: -40~80℃
适用于汽车维护中心、工厂车间、各种远离气源、电源的工作场所

Unique highly wearing resistant multi-seal technology, no gas leak
Unique multiple electrical connection mechanism, ensuring stable power supply transmission
Unique adjustable hose & cable contractile power structure
Provided with unique cold-proof, wear-resistant, oil proof cable of high performance
The product is made of polymers, with fully sealed structure and stylish design
Hose & cable Automatically arranged, prevent the hose & cable from winding
Hose & cable by stainless steel outlet, reducing the friction
The steel main shaft is not easy to break, and is durable
Bearing balls on the two sides make it more lubricant, prolonging the service life of product
The steel pawl seat is hard for deformation and mal-position
180 rotatable, more convenient for use
Provided with movable mounting support, easy for mounting, dismantling and movement
Self-locking quick connector specialized for auto maintenance is resistant to high pressure
Work pressure: 1~16KGF/cm², work temperature: -40~80℃
Suitable for auto maintenance center, workshop, and other working place far away from air supply and power supply

技术参数 Parameters

类型 Type	型号 Model	线管规格 Hose & Cable	线管材质 Hose & Cable Material	装箱尺寸/台 Packing size/sets	装箱数量 QTY
水管式 Water hose type	SPS-612	Φ8×Φ12mm×12m	PU 夹纱 PU gripper	39×33×16cm	4台/箱 Sets/box
气管式 Air hose type	SPS-612	Φ8×12mm×12m	PU 夹纱 PU gripper	39×33×16cm	4台/箱 Sets/box
气管式 Air hose type	SPS-615	Φ6.5×Φ10mm×15m	PU 夹纱 PU gripper	39×33×16cm	4台/箱 Sets/box
插座式 Socket type	SPS-611A	Φ1.5mm ² ×15m×2	塑料Plastic	39×33×16cm	4台/箱 Sets/box
工作灯式 Working-lamp type	SPS-612A	Φ1.5mm ² ×15m×2	塑料Plastic	39×33×16cm	4台/箱 Sets/box