



IP66
PROTECTION
DEGREE

产品特性 PRODUCT FEATURES

- 采用高强度ABS、PC材料制成，重量只有铁制箱子的1/4左右，便于搬运和操作，耐腐蚀，绝缘性佳。
- 产品经过严格的品质检测，其防水、防尘等级达到IP66（检测报告备案）。
- 适用于机场、地铁站、按钮盒、小型终端机、信号机箱、继电器、传感器、通信接线盒等设备。
- It is made from high strength ABS/PC material, weights about 1/4 of the metal box, easy handling and operating, corrosion resistance, good insulation.
- The product has passed strict waterproof and dustproof test, it reach IP66.
- It can be used in airport, subway station, and it can be pushbutton box, terminal box, signal box, relays box, sensor box and communication junction box and so on.

技术参数 TECHNICAL DATA

尺寸Size	ABS	PC/ABS	PC	PC
宽x高x深度(mm) WxHxD(mm)	灰色盖子 Solid cover	透明盖子 Clear cover	灰色盖子 Solid cover	透明盖子 Clear cover
190×190×130	DS-AG-1919	DS-AT-1919	DS-PG-1919	DS-PT-1919
280×190×130	DS-AG-2819	DS-AT-2819	DS-PG-2819	DS-PT-2819
280×190×180	DS-AG-2819-1	DS-AT-2819-1	DS-PG-2819-1	DS-PT-2819-1
380×190×130	DS-AG-3819	DS-AT-3819	DS-PG-3819	DS-PT-3819
380×190×180	DS-AG-3819-1	DS-AT-3819-1	DS-PG-3819-1	DS-PT-3819-1
280×280×130	DS-AG-2828	DS-AT-2828	DS-PG-2828	DS-PT-2828
380×280×130	DS-AG-3828	DS-AT-3828	DS-PG-3828	DS-PT-3828
380×280×180	DS-AG-3828-1	DS-AT-3828-1	DS-PG-3828-1	DS-PT-3828-1
560×380×180	DS-AG-5638	DS-AT-5638	DS-PG-5638	DS-PT-5638
560×380×265	DS-AG-5628	DS-AT-5628	DS-PG-5628	DS-PT-5628
温度 Temperature	AG(ABS)	PG(PC/ABS)	PCG(PBT/PC)	Clear cover (Polycarbonate)
短时间 Short time	-40℃~+100℃	-40℃~+90℃	-40℃~+100℃	-40℃~+132℃
连续 Continuous	-40℃~+80℃	-40℃~+85℃	-40℃~+75℃	-40℃~+130℃