




外形尺寸 DIMENSIONS



RoHS
CE

IP68防尘、防水测试合格

产品特性 PRODUCT FEATURES

- 材料: 黄铜镀镍
 - 夹紧件: 尼龙PA (UL File NO:E 240925)
 - 密封件: 丁腈橡胶 (NBR)
耐候橡胶 (EPDM)
 - 防护等级: IP68 (旋紧部位)
 - 环境温度: -40°C至100°C, 短时至120°C
- Material: brass plating nickel
 - Clamping: PA (UL File NO:E 240925)
 - Rubber gasket: Nitrile rubber(NBR)
Protection Grade: IP68
 - Ambient temperature: stick~40°C
to 100°C,for short time 120°C,Dynamic
-20°C to 80°C,For short time 100°C

技术参数 TECHNICAL DATA

型号	∅k	GL	H	ψ	AG	订货号
Model	mm	mm	mm	mm	mm	Art.No.
PG7	3-6.5	5	19	14	12.5	P070806
PG7	2-5	5	19	14	12.5	P070505
PG9	4-8	6	20	17	15.2	P090608
PG9	2-6	6	20	17	15.2	P090606
PG11	5-10	6	21	20	18.6	P110610
PG11	3-7	6	21	20	18.6	P110607
PG13.5	6-12	6.5	22	22	20.4	P130712
PG13.5	5-9	6.5	22	22	20.4	P130709
PG16	10-14	6.5	23	24	22.5	P160714
PG16	7-12	6.5	23	24	22.5	P160712
PG21	13-18	7	25	30	28.3	P210718
PG21	9-16	7	25	30	28.3	P210716
PG29	18-25	8	29	40	37	P290825
PG29	13-20	8	29	40	37	P290820
PG36	22-32	8	35	50	47	P360832
PG36	20-26	8	35	50	47	P360826
PG42	32-38	9	37	57	54	P420938
PG42	25-31	9	37	57	54	P420931
PG48	37-44	10	38	64	59.3	P481044
PG48	29-35	10	38	64	59.3	P481035